

RO Membrane

-NSF certified Membranes



Quick Change RO Membrane

GT-R50 / GT-R75 / GT-R100 / GT-R200



Specification

Model No	GT-R50	GT-R75	GT-R100	GT-R200
Product Name	Quick Change RO Membrane			
Membrane Size	1812-50	1812-75	1812-100	1812-200
Application	Membrane for RO Drinking Water System			
Output Capacity	50GPD	75GPD	100GPD	200GPD
Rejection Rate	95% ~97%			
Feed Water Quality	TDS < 500 ppm			
Maximum Feed Water SDI	5			
Maximum Operating Pressure	100 psi			
Maximum Temperature	120 °F			



High Flow Commercial RO Membrane



Residential NSF RO Membrane

Model No	ULP21-4021	ULP21-4040	ULP-1812-50	ULP-1812-75	ULP-2012-100
Product Name	High Flow Commercial RO Membrane		Residential NSF RO Membrane		
Brand	Vontron				
Application	Membrane for Big Flow RO Water System		Membrane for RO Drinking Water System		
Membrane Size	4021 (4" diameter, 21" length)	4040 (4" diameter, 40" length)	1812-50	1812-75	2012-100
Output Capacity	800 GPD	1500 GPD	50 GDP	75 GPD	100 GPD
Rejection Rate	98% ~99%		95% ~97%		
Recovery Rate	8%	15%	—	—	—
Certification	NSF certified				
Feed Water Quality	TDS < 2000 ppm		TDS < 500 ppm		
Maximum Operating Pressure	100 psi				
Maximum Temperature	120 °F				
Country of Origin (CO)	China				

GPD=gallon per day